Engineering Specification

Job Name	Contractor
Job Location	Approval
Engineer	Contractor's P.O. No.
Approval	Representative
	SKU

${f AD} \; {f FREE}^*$

Swirl Hose Water Supply Lines

Sizes: 1/4" to 1/2"

The Dormont Swirl Hose quickly and easily connects water-fed appliances and equipment to the water supply line, providing trouble-free installations that save you time and money. Applications include ice machines, coffee makers, steamers, combi-ovens, and drain lines.

Features

 Tubing Durable, Retractable NSF Approved

Polyurethane

 Hose End Fittings Brass Pipe Elbows Brass

• Optional Double Shut-off Quick Disconnect

Stainless Steel ISO 7241-1, Series B coupling and nipple both valved to prevent water flow when disconnected

Specifications

 Pressure 100psi MAX

 Temperature Water 160°F MAX (71°C)

Approvals & Certifications

NSF/ANSI 169 - Special Purpose Food Equipment and Devices

NSF/ANSI 372 - Drinking Water System Components -

Lead Content



NSF



Male x Female Pipe Elbow



LEAD FREE*



Model 72-2125 as shown



The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of this product.

*The wetted surface of this product contacted by consumable water contains less than 0.25% of lead by weight.



Configurations







Male x Female Pipe Elbow



Male x Male Pipe Elbow



Male Pipe x Female Flare Adapter



Double Shut-off Quick Disconnect

PRODUCT CONFIGURATION	SWIRL HOSE END FITTING THREADS	FEMALE FLARE Adapter Threads	PIPE ELBOW THREADS	QUICK DISCONNECT THREADS	1/4" ID	3/8" ID	1/2" ID
Swirl Hose with Double Shut-off Quick Disconnect and Male x Female Pipe Elbow	Female Swivel Nut x Fixed Male NPT	N/A	Male NPT x Female NPT	Female NPT	71-1115-XX	72-2125-XX	N/A
Swirl Hose with Double Shut-off Quick Disconnect and Male x Male Pipe Elbow	Female Swivel Nut x Fixed Male NPT	N/A	Male NPT x Male NPT	Female NPT	N/A	N/A	73-3135-XX
Swirl Hose with Male x Female Pipe Elbow	Female Swivel Nut x Fixed Male NPT	N/A	Male NPT x Female NPT	N/A	71-1114-XX	72-2124-XX	N/A
Swirl Hose with Male x Male Pipe Elbow	Female Swivel Nut x Fixed Male NPT	N/A	Male NPT x Male NPT	N/A	N/A	N/A	73-3134-XX
Swirl Hose with Male x Female Pipe Elbow and 1/4" Female Flare Adapter	Female Swivel Nut x Fixed Male NPT	Male NPT x 1/4" Female Flare	Male NPT x Female NPT	N/A	71-1118-XX	N/A	N/A
Swirl Hose with Male x Female Pipe Elbow and 3/8" Female Flare Adapter	Female Swivel Nut x Fixed Male NPT	Male NPT x 3/8" Female Flare	Male NPT x Female NPT	N/A	71-1128-XX	N/A	N/A
Double Shut-off Quick Disconnect	N/A	N/A	N/A	Female NPT	LFW25QD	LFW37QD	LFW50QD

^{*} Where XX = Overall length in inches available in 48" and 72"

Typical Installation





Swirl Hose Water Supply Lines

The Dormont Swirl Hose quickly and easily connects waterfed appliances and equipment to the water supply line, providing trouble-free installations that save you time and money. Applications include ice machines, coffee makers, steamers, combi-ovens, and drain lines..



Double Shut-off Quick Disconnect

Stainless Steel ISO 7241-1, Series B coupling and nipple both valved to prevent water flow when disconnected.



We guarantee our LEAD FREE* Swirl Hose Water Supply Lines for 5 years from original installation.



USA: T: (800) 367-6668 • F: (724) 733-4808 • Dormont.com
Canada: T: (905) 332-4090 • F: (905) 332-7068 • Dormont.ca
Latin America: T: (52) 81-1001-8600 • Dormont.com

ES-D-FS-Swirl Hose 2028 © 2020 Dormont