

Doyon Retarder Proofer KDPR Series



KDPR33



Ships Knocked Down

Features

- Digital touchscreen with programmable recipes
- Designed in either 1, 2, 3 rack width
- Expandable to 1, 2, 3 rack depth
- Proofing range from room temperature to 110°F (43°C)
- Relative humidity up to 95%
- KDPR retarding temperature range: 36°-45° F (2.2°C-7.2°C)
- Easy connect to utilities; built-in drain, single water line connection
- Available in left or right hinge door (KDPR11, KDPR12, KDPR13)
- R134a environmentally safe refrigeration
- Water inlet: 1/4" tube, 15-25 PSI (pressure)

Construction

- Stainless steel construction
- Fully insulated
- Ships knockdown
- One Year Labor & Two Year Parts Warranty



Options

- Water Filter (50-1530) (recommended)
- Pass through configuration—suffix PT (Note: single control panel only on front & door hinged same on single unit only)
- Door bumpers (DB)
- Facility installation and startup
- Factory startup (installation not included)
- Stainless steel floor with drain (Note: contact factory to verify if floor is required for use with unit)

Specifications

Model	Crated Weight lbs (kg)	Overall Dimensions in (mm)			Single End Loaded Rack Capacity	Single Side Loaded Rack Capacity	Double Rack Capacity	Door Opening in (mm)		Water Inlet in (mm)	Electrical System			
		W	D	H				L	H		Phase	Volts	Amps	kW
KDPR11	400 (182)	42" (1066)	47 3/8" (1203)	101" (2565)	1	2	1	27" (686)	73 1/2" (1867)	1/4" (6)	1 1	208 240	24 21	5
KDPR12	500 (227)	42" (1066)	87 3/8" (2219)	101" (2565)	3	4	2	32 1/2" (826)	73 1/2" (1867)	1/4" (6)	1 1	208 240	24 21	5
KDPR13	700 (318)	42" (1066)	127 3/8" (3225)	101" (2565)	5	6	3	27" (686)	73 1/2" (1867)	1/4" (6)	1 1	208 240	48 42	10
KDPR21	800 (363)	74 1/2" (1892)	47 3/8" (1203)	101" (2565)	3	4	2	27" (686)	73 1/2" (1867)	1/4" (6)	1 1	208 240	24 21	5
KDPR22	900 (409)	74 1/2" (1892)	87 3/8" (2219)	101" (2565)	8	8	4	32 1/2" (826)	73 1/2" (1867)	1/4" (6)	1 1	208 240	48 42	10
KDPR23	1230 (558)	74 1/2" (1892)	127 3/8" (3225)	101" (2565)	12	12	6	27" (686)	73 1/2" (1867)	1/4" (6)	1 3	208/240 208/240	72/63 42/36	15
KDPR31	1472 (668)	107" (2718)	47 3/8" (1203)	101" (2565)	4	6	3	27" (686)	73 1/2" (1867)	1/4" (6)	1	208 240	48 42	10
KDPR32	1832 (831)	107" (2718)	87 3/8" (2219)	101" (2565)	11	12	6	27" (686)	73 1/2" (1867)	1/4" (6)	1 3	208/240 208/240	72/63 42/36	15
KDPR33	2479 (1125)	107" (2718)	127 3/8" (3235)	101" (2565)	16	18	9	32 1/2" (826)	73 1/2" (1867)	1/4" (6)	1 3	208/240 208/240	72/63 42/36	15